

Lucas-Milhaupt Clean & Bright 6 Tin/ Silver Solder

Category: Metal, Nonferrous Metal, Solder/Braze Alloy, Tin Alloy

Material Notes:

Characteristics:This alloy is considered to be high strength solders. It has much higher creep strengths than the tin/lead solders. It is a good color match for stainless steel, and used with the proper flux will wet stainless very well. SN 94 is less fluid respectively, and will bridge larger gaps because of their wide plastic range. Joint clearances of 0.1 to 0.15mm (.003 to .005 in) are optimum, but larger variations can still produce sound joints. Flux is required and proper selection will depend upon base metals to be joined. Specifications: This alloy conforms to the following specification: ASTM B32-Sn94 Information provided by Lucas-Milhaupt, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lucas-Milhaupt-Clean-Bright-6-Tin-Silver-Solder.php

Physical Properties	Metric	English	Comments
Density	7.45 g/cc	0.269 lb/in³	

Thermal Properties	Metric	English	Comments
Melting Point	221 - 280 °C	430 - 536 °F	
Solidus	221 °C	430 °F	Melting Point
Liquidus	280 °C	536 °F	Flow Point

Component Elements Properties	Metric	English	Comments
Silver, Ag	6.0 %	6.0 %	
Tin, Sn	94 %	94 %	

Descriptive Properties	Value	Comments
Color	White	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China