

Lucas-Milhaupt Dry Flux Silver Brazing Flux

Category : Metal , Nonferrous Metal , Solder/Braze Alloy

Material Notes:

Dry Flux is a premium quality brazing flux in powdered form consisting of a unique combination of borates and fluorides for use with torch, induction, furnace, resistance, dip and other heating methods. For convenience in applying, flux may be diluted with water. Information provided by Lucas-Milhaupt Warwick, LLC (formerly Wolverine Joining Technologies).

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lucas-Milhaupt-Dry-Flux-Silver-Brazing-Flux.php

Physical Properties	Metric	English	Comments
Water Absorption	<= 5.0 %	<= 5.0 %	
pH	8.0	8.0	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	871 Â°C	1600 Â°F	
Minimum Service Temperature, Air	593 Â°C	1100 Â°F	

Descriptive Properties	Value	Comments
Composition	Potassium salts of fluorine and boric acid	
Type	Powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China