

Lucobit Lucobatch® 1850 T10 Polyolefin TPO Granules

Category : Polymer , Thermoplastic , Polyolefin

Material Notes:

Lucobatch® 1850 T10 is a highly stabilized polyolefin based TPO granules. Lucobatch® 1850 T10 is employed as a master batch. Blended with suitable polyolefins, tunnel membranes are built of Lucobatch® 1850 T10/ T20/T100. Tunnel membranes which are built by blending Lucobatch® 1850 T10 have convincing properties on account of : Outstanding breaking strength, extension, flexibility Long-term resistance of at least 10 years Good tenacity, high biaxial extensibility and flexibility even at low temperatures Information provided by Lucobit AG

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lucobit-Lucobatch-1850-T10-Polyolefin-TPO-Granules.php

Physical Properties	Metric	English	Comments
Density	1.29 g/cc	0.0466 lb/in ³	ISO 1183
Melt Flow	2.84 g/10 min @Load 2.16 kg, Temperature 190 °C	2.84 g/10 min @Load 4.76 lb, Temperature 374 °F	ISO 1133

Processing Properties	Metric	English	Comments
Processing Temperature	150 - 200 °C	302 - 392 °F	Profiles
	160 - 230 °C	320 - 446 °F	Membranes
	160 - 270 °C	320 - 518 °F	Coatings

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China