

## Lushan M-2 Adhesive Resin for Barrier Container and Tube

Category : Polymer , Adhesive

**Material Notes:**

Adhesive resin Lushan series for barrier container and tube is used for bonding a wide variety of materials, Itâ€™s most often used to adhering PE and EVOH, PP and EVOH, etc. Adhesive resins Lushan series for barrier container and tube can be used in a variety of co-extrusion coating and laminating applications, such as high barrier HDPE/EVOH oil tank, HDPE/polyamide bottles for agricultural chemicals and other composite barrier bottles for food packaging, etc. Adhesive resin Lushan series for food package complies with FDA 21CFR175.105 and suitable for indirect food contact. Application: Cosmetic Tube Information provided by Lushan

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lushan-M-2-Adhesive-Resin-for-Barrier-Container-and-Tube.php](http://www.lookpolymers.com/polymer_Lushan-M-2-Adhesive-Resin-for-Barrier-Container-and-Tube.php)

Physical Properties	Metric	English	Comments
Density	0.930 g/cc	0.0336 lb/in <sup>3</sup>	ASTM D1505
Melt Index of Compound	2.5 g/10 min	2.5 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	12.0 MPa	1740 psi	ASTM D638
Elongation at Break	500 %	500 %	ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	128 Â°C	262 Â°F	ASTM D2117
Vicat Softening Point	70.0 Â°C	158 Â°F	ASTM D1525
Brittleness Temperature	-70.0 Â°C	-94.0 Â°F	ASTM D746

Descriptive Properties	Value	Comments
Appearance	Transparent granule particles	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China