

LyondellBasell AdsyL₅C30F Polyolefin

Category : Polymer , Film , Thermoplastic , Polyolefin , Polyolefin, Film Grade , Polyolefin, Film Grade (Polyolefin)

Material Notes:

Description: AdsyL₅C30F is a new thermoplastic polyolefin which has been designed as a BOPP sealing layer material with exceptionally low sealing temperature. It features a high clarity and gloss, a low haze, a wide hot-tack range and a Seal-Initiation Temperature (SIT) of 106°C measured on 30 µm film. It does not contain any slip nor anti-blocking agents and is therefore suitable for the production of metallized film. AdsyL₅C30F can be processed on both stenter and double bubble equipment. The composition of the product complies with FDA norms and with regulations in force in major European concerning food contact applications. Information provided by Basell.

Order this product through the following link:

http://www.lookpolymers.com/polymer_LyondellBasell-AdsyL-5-C-30-F-Polyolefin.php

Physical Properties	Metric	English	Comments
Density	0.890 g/cc	0.0322 lb/in ³	ISO 1183
Melt Flow	5.5 g/10 min @Load 2.16 kg, Temperature 230 °C	5.5 g/10 min @Load 4.76 lb, Temperature 446 °F	Condition L; ISO 1133

Mechanical Properties	Metric	English	Comments
Heat Seal Strength Initiation Temperature	106.1 °C	223.0 °F	1.2 mil

Thermal Properties	Metric	English	Comments
Melting Point	135 °C	275 °F	MTM 15902

Optical Properties	Metric	English	Comments
Haze	1.5 %	1.5 %	MTM 17031, 50 µm film

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China