

## Mallard Creek Polymers ROVENE® 4150 SBR Latex

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE) , Styrene Butadiene Rubber

## Material Notes:

Emulsifiers

ROVENE® 4150 is a medium-firm, self-XLing, carboxylated styrene-butadiene (SBR) latex emulsion. Its styrene content (55%) permits its use in formulating carpet and flooring mastics. This versatile polymer is also used in a variety of textile and non-woven applications. ROVENE® 4150 offers finished properties of high tensile strength and good water resistance.APPLICATIONS: ROVENE® 4150 is recommended for carpet and floor mastics along with several textile and non-woven applications.Information provided by Mallard Creek Polymers

## Order this product through the following link: http://www.lookpolymers.com/polymer\_Mallard-Creek-Polymers-ROVENE-4150-SBR-Latex.php

Physical Properties	Metric	English	Comments
Solids Content	50 - 52.5 %	50 - 52.5 %	
Particle Size	0.15 µm	0.15 µm	
рН	9.0 - 10	9.0 - 10	
Brookfield Viscosity	100 - 500 cP	100 - 500 cP	#2/20 rpm

Thermal Properties	Metric	English	Comments
Glass Transition Temp, Tg	-14.0 °C	6.80 °F	

Metric	English	Comments	
55 %	55 %		
	Value	Comments	
		55 % 55 %	55 % 55 %

Anionic

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China