

## Mallard Creek Polymers ROVENE® 4487 SBR Latex

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE), Styrene Butadiene Rubber

## **Material Notes:**

ROVENE® 4487 is a carboxylated styrene-butadiene emulsion that has a firm hand with excellent strength properties. This binder is a low VOC containing latex that is cross-linkable with external cross-linking agents. ROVENE® 4487 can be compounded to high solids using calcium carbonate, clays, and alumina trihydrate as fillers; sodium polyacrylate thickeners are commonly used to obtain the required application viscosity. ROVENE® 4487 imparts good wet/dry tensile strength, and has good adhesion to a wide variety of surfaces. This adhesion contributes to the good tuft binds and excellent delaminations in carpet applications. APPLICATIONS: ROVENE® 4487 is recommended for use in carpet and nonwoven backcoatings, and has found applications in the adhesive industry. Information provided by Mallard Creek Polymers

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Mallard-Creek-Polymers-ROVENE-4487-SBR-Latex.php

Physical Properties	Metric	English	Comments
Solids Content	54.5 - 55.5 %	54.5 - 55.5 %	
Particle Size	0.18 Âμm	0.18 µm	
рН	7.0 - 7.5	7.0 - 7.5	
Brookfield Viscosity	200 - 1500 cP	200 - 1500 cP	#2/20 rpm

Thermal Properties	Metric	English	Comments
Glass Transition Temp, Tg	11.0 °C	51.8 °F	

Chemical Properties	Metric	English	Comments
Styrene Content	62 %	62 %	

Descriptive Properties	Value	Comments
Emulsifiers	Anionic	

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China