

MarkeTech Cu/Mo/Cu 1:5:1 Laminated Sheet

Category: Metal, Metal Matrix Composite, Nonferrous Metal, Molybdenum Alloy

Material Notes:

Cu/MoCu sheets have very high in-plane thermal conductivity provide by layers of Cu and low CTEs provided by the inner layer of molybdenum. These laminated sheets spread heat from a concentrated heat source and subsequently dissipate the heat through the layers. Used as heat sinks. Data provided by the supplier, MarkeTech International.

Order this product through the following link:

http://www.lookpolymers.com/polymer_MarkeTech-CuMoCu-151-Laminated-Sheet.php

Physical Properties	Metric	English	Comments
Density	9.74 - 9.94 g/cc	0.352 - 0.359 lb/in³	

Thermal Properties	Metric	English	Comments
CTE, linear	6.20 - 6.60 µm/m-°C	3.44 - 3.67 µin/in-°F	
	@Temperature 20.0 - 100 °C	@Temperature 68.0 - 212 °F	
Thermal Conductivity	165 - 170 W/m-K	1150 - 1180 BTU-in/hr- ft²-°F	z direction
	195 - 200 W/m-K	1350 - 1390 BTU-in/hr- ft²-°F	x-y direction
Maximum Service Temperature, Air	850 °C	1560 °F	resists repeated cycles

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China