

MarkeTech Repton 202 Aluminum Oxide

Category : Ceramic , Oxide , Aluminum Oxide

Material Notes:

REPTON setter tiles, kiln furniture, and special fixtures are lightweight, ridge, and high strength ceramics that resist distortion and spalling, even when thermal cycled many times. They are available with a smooth or a unique textured surface that permits pinpoint contact with the load. Sticking can be eliminated as well as providing a surface that breathes, allowing gasses from the ceramic to escape. Applications include firing ceramic capacitors, SOFCs, PZTs, hard and soft ferrites, co-fired substrates and powdered metals. REPTON is available in a wide range of compositions that include a range of alumina, mullite/alumina, zirconia, cordierite, magnesia, and aluminum titanate.

Order this product through the following link:

http://www.lookpolymers.com/polymer_MarkeTech-Repton-202-Aluminum-Oxide.php

Physical Properties	Metric	English	Comments
Bulk Density	1.80 g/cc	0.0650 lb/in ³	
Density	4.00 g/cc	0.145 lb/in ³	calculated from bulk density after subtracting pore volume
Porosity	55 %	55 %	

Mechanical Properties	Metric	English	Comments
Flexural Strength	>= 22.0 MPa	>= 3190 psi	

Component Elements Properties	Metric	English	Comments
Al ₂ O ₃	99.6 %	99.6 %	

Descriptive Properties	Value	Comments
Spall Resist	400 ^o C	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China