

MarkeTech Repton 914 Magnesia MgO

Category: Ceramic, Oxide, Magnesium Oxide

Material Notes:

REPTON setter tiles, kiln furniture, and special fixtures are lightweight, ridge, and high strength ceramics that resist distortion and spalling, even when thermal cycled many times. They are available with a smooth or a unique textured surface that permits pinpoint contact with the load. Sticking can be eliminated as well as providing a surface that breathes, allowing gasses from the ceramic to escape. Applications include firing ceramic capacitors, SOFCs, PZTs, hard and soft ferrites, co-fired substrates and powdered metals. REPTON is available in a wide range of compositions that include a range of alumina, mullite/alumina, zirconia, cordierite, magnesia, and aluminum titanate.

Order this product through the following link:

http://www.lookpolymers.com/polymer_MarkeTech-Repton-914-Magnesia-MgO.php

Physical Properties	Metric	English	Comments
Bulk Density	3.10 g/cc	0.112 lb/in³	
Density	3.48 g/cc	0.126 lb/in³	calculated from bulk density after subtracting pore volume
Porosity	11 %	11 %	

Mechanical Properties	Metric	English	Comments
Flexural Strength	>= 98.0 MPa	>= 14200 psi	

Thermal Properties	Metric	English	Comments
CTE linear	12.0 Âμm/m-°C	6.67 µin/in-°F	
CTE, linear	@Temperature 300 °C	@Temperature 572 °F	
	14.0 Âμm/m-°C	7.78 µin/in-°F	
	@Temperature 900 °C	@Temperature 1650 °F	

Component Elements Properties	Metric	English	Comments	
MgO	100 %	100 %		

Descriptive Properties	Value	Comments
Spall Resist	300°C	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com



Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China