

Michelman® HydroGrease Whiteâ,,¢ 22 White coating

Category: Fluid, Other Engineering Material, Additive/Filler for Polymer

Material Notes:

Description: High performance water and grease resistant white coating Usage: HydroGrease Whiteâ,,¢ 22 is a white coating which imparts water and grease resistance to the substrate. This coating is hot melt and cold set gluable. Application data: HydroGrease Whiteâ,,¢ 22 is best applied by rod coater at the wet end of the corrugator. Food Contact Information when manufactured in the USA: FDA: 176.170: Components of paper and paperboard in contact with aqueous and fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with dry foods. (Restricted) Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-HydroGrease-White-22-White-coating.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.44 - 1.46 g/cc	1.44 - 1.46 g/cc	
pH	8.0 - 9.5	8.0 - 9.5	
Brookfield Viscosity	400 - 800 cP	400 - 800 cP	Spindle # 3, rpm 60
Viscosity Measurement	16 - 22	16 - 22	[sec], EZ cup, Cup # 3

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	

Descriptive Properties	Value	Comments
Appearance	White, opaque liquid	
Solids Type	Polymer/Pigment	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China