## Michelman® Michem® Coat 40Y Water resistant, cold set and hot melt gluable coating

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer

## Material Notes:

Description: Water resistant, cold set and hot melt gluable coatingUsage: Michem® Coat 40Y is a versatile water resistant coating. It is gluable with a wide range of water based and hot melt adhesives. Application data: Michem® Coat 40Y can be applied at the corrugator and off-line using either a blade or a rod coater. Michem® Coat is typically used for: Bakery products; Packaged butter; Pizza boxes; Machinery: Electrical components; Metal parts and Sensitive papersFood Contact Information when manufactured in the USA and Belgium: FDA: 176.170: Components of paper and paperboard in contact with aqueous and fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous for a fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous for a fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous for a fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous fatty foods (Restricted) 176.180: Components of paper and paperboard in contact with aqueous fatty foods (Restricted) 176.180: Components of paper foods (Restricted) 176.180: Components of paper foods (Restricted) 176.180: Components fatty foods (Restricted) 176.180: Components foods (Restricted) 176

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Michelman-Michem-Coat-40Y-Water-resistant-cold-set-and-hot-melt-gluable-coating.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.01 - 1.03 g/cc	1.01 - 1.03 g/cc	
рН	9.0 - 10	9.0 - 10	
Brookfield Viscosity	250 - 800 cP	250 - 800 cP	Spindle # 3, rpm 60
Viscosity Measurement	20 - 40	20 - 40	[sec], EZ cup, Cup # 2

Descriptive Properties	Value	Comments	
Appearance	Milky white, semi-viscous liquid		
Solids Type	Acrylic/Wax		

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China