## Michelman® Michem® Coat 95 Water and grease resistant, heat sealable coating

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer

## **Material Notes:**

Description: Water and grease resistant, heat sealable coatingUsage: Michem® Coat 95 is a good multi-purpose coating that provides excellent water, oil and grease resistance. This product is heat sealable and cold set gluable as well.Application data: Michem®Coat 95 is designed to be flexo or gravure applicable. For use as a heat seal coating on paper at a dry coating weight between 4 - 6gsm is recommended. Typical sealing conditions are 140-200C, 4 bar pressure, 1 sec dwell time.Michem® Coat is typically used for: Bakery products; Packaged butter; Pizza boxes; Machinery: Electrical components; Metal parts and Sensitive papersFood Contact Information when manufactured in Belgium:FDA:175.320: Resinous and polymeric components of coatings for polyolefin films. (Restricted)176.170: Components of paper and paperboard in contact with aqueous and fatty foods176.180: Components of paper and paperboard in contact with dry foodsInformation provided by Michelman®

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Michelman-Michem-Coat-95-Water-and-grease-resistant-heat-sealable-coating.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.00 - 1.10 g/cc	1.00 - 1.10 g/cc	
рН	7.0 - 9.0	7.0 - 9.0	
Brookfield Viscosity	300 - 750 cP	300 - 750 cP	Spindle # 3, rpm 20

Descriptive Properties	Value	Comments
Appearance	Off-white liquid	
Solids Type	Acrylic Styrene Copolymer	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China