

Michelman® Michem® Emulsion 21930 Anionic Tung Oil emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Description: Anionic Tung Oil emulsionUsage: Michem® Emulsion 21930 is a Tung Oil emulsion that contains 99.5% natural ingredients. It is used as an additive that imparts good water bead to wood and concrete coatings. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foamInformation provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Emulsion-21930-Anionic-Tung-Oil-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.970 - 0.990 g/cc	0.970 - 0.990 g/cc	
Volatiles	69.5 - 70.5 %	69.5 - 70.5 %	
pH	<= 7.0	<= 7.0	Recommended pH of system
	8.0 - 9.0	8.0 - 9.0	
Brookfield Viscosity	<= 200 cP	<= 200 cP	Spindle # 2, rpm 60

Descriptive Properties	Value	Comments
Appearance	Off-white liquid	
Emulsifier Charge	Anionic	
Solids Type	Organic	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China