

Michelman® Michem® Emulsion 32535 Nonionic, polyethylene emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

Description: Nonionic, polyethylene emulsion Usage: Michem® Emulsion 32535 is best used as an additive in water based coatings where improved slip, rub resistance, hardness and/or block resistance is needed. This wax emulsion can be used as an additive to paper coatings, wood coatings, metal coatings, overprint varnishes, floor polish and other water based coatings where slip and hardness are required, without significant degradation of gloss. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foam Food Contact Information when manufactured in the USA, Belgium and Singapore: FDA: 175.105:

Components of adhesives. Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Emulsion-32535-Nonionic-polyethylene-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.00 - 1.02 g/cc	1.00 - 1.02 g/cc	
Volatiles	64.5 - 65.5 %	64.5 - 65.5 %	
pH	<= 7.0	<= 7.0	Recommended pH of system
	9.0 - 10.5	9.0 - 10.5	
Brookfield Viscosity	<= 50 cP	<= 50 cP	Spindle # 2, rpm 60

Descriptive Properties	Value	Comments
Appearance	Light amber liquid	
Emulsifier Charge	Nonionic	
Solids Type	High Density Polyethylene	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China