

Michelman® Michem® Emulsion 34935 Anionic paraffin/ethylene acrylic acid wax emulsion

Category: Fluid, Other Engineering Material, Additive/Filler for Polymer, Polymer, Thermoplastic, Ethylene Acrylic Acid

Material Notes:

Description: Anionic paraffin/ethylene acrylic acid wax emulsionUsage: Michem® Emulsion 34935 is best used as an additive where excellent water beading properties are required It is primarily used for its water resistant properties in the wood coatings and paper coatings markets. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foamFood Contact Information when manufactured in the USA:FDA:175.105: Components of adhesives.Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Emulsion-34935-Anionic-paraffinethylene-acrylic-acid-wax-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.950 - 0.970 g/cc	0.950 - 0.970 g/cc	
Volatiles	64.5 - 65.5 %	64.5 - 65.5 %	
рН	<= 7.0	<= 7.0	Recommended pH of system
	8.5 - 9.5	8.5 - 9.5	
Brookfield Viscosity	400 - 1800 cP	400 - 1800 cP	Spindle # 3, rpm 60

Descriptive Properties	Value	Comments
Appearance	White, viscous liquid	
Emulsifier Charge	Anionic	
Solids Type	Paraffin/Ethylene Acrylic Acid Copolymer blend	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China