

Michelman® Michem® Emulsion 41740 Nonionic, polyethylene emulsion

Category: Fluid, Other Engineering Material, Additive/Filler for Polymer, Polymer, Thermoplastic, Polyethylene (PE)

Material Notes:

Description: Nonionic, polyethylene emulsionUsage: Michem® Emulsion 41740 is used for release and water resistance in specialty coated films and papers. It is also an effective tactile modifier for interior automotive coatings. It can help give synthetic materials the draggy feel of leather. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foamInformation provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Emulsion-41740-Nonionic-polyethylene-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.950 - 0.970 g/cc	0.950 - 0.970 g/cc	
Volatiles	59.5 - 60.5 %	59.5 - 60.5 %	
рН	1.0 - 12	1.0 - 12	Recommended pH of system
	4.0 - 10	4.0 - 10	
Brookfield Viscosity	<= 200 cP	<= 200 cP	Spindle # 2, rpm 60

Descriptive Properties	Value	Comments
Appearance	Milky white liquid	
Emulsifier Charge	Nonionic	
Solids Type	Polyethylene	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China