

Michelman® Michem® Emulsion 52137 Nonionic polyethylene emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

Description: Nonionic polyethylene emulsion Usage: Michem® Emulsion 52137 as an additive, provides lubricity and is effective as a high temperature mold release for metal dies. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foam Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Emulsion-52137-Nonionic-polyethylene-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.980 - 1.00 g/cc	0.980 - 1.00 g/cc	
Volatiles	62.5 - 63.5 %	62.5 - 63.5 %	
pH	2.0 - 12	2.0 - 12	Recommended pH of system
	8.5 - 9.5	8.5 - 9.5	
Brookfield Viscosity	<= 100 cP	<= 100 cP	Spindle # 2, rpm 60

Descriptive Properties	Value	Comments
Appearance	Light yellow, translucent liquid	
Emulsifier Charge	Nonionic	
Solids Type	Polyethylene	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China