

Michelman® Michem® Emulsion 52830 Anionic polyethylene wax emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

Description: Anionic polyethylene wax emulsion Usage: Michem® Emulsion 52830 as an additive provides water resistance for stucco coatings as well as release for anti-graffiti coatings. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foam Food Contact Information when manufactured in Belgium: FDA:175.105:

Components of adhesives Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Emulsion-52830-Anionic-polyethylene-wax-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.950 - 0.970 g/cc	0.950 - 0.970 g/cc	
Volatiles	69.5 - 70.5 %	69.5 - 70.5 %	
pH	>= 7.0	>= 7.0	Recommended pH of system
	8.8 - 9.8	8.8 - 9.8	
Brookfield Viscosity	30 - 100 cP	30 - 100 cP	Spindle # 2, rpm 60

Descriptive Properties	Value	Comments
Appearance	Amber, translucent liquid	
Emulsifier Charge	Anionic	
Solids Type	Polyethylene blend	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China