

## Michelman® Michem® Emulsion 61335 Anionic polyethylene emulsion

Category: Fluid, Other Engineering Material, Additive/Filler for Polymer, Polymer, Thermoplastic, Polyethylene (PE)

## **Material Notes:**

Description: Anionic polyethylene emulsionUsage: Michem® Emulsion 61335 is an additive which provides excellent slip and mar resistance and anti-blocking properties. This product can be used as a release and slip aid in adhesives and paper coatings. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foamFood Contact Information when manufactured in Belgium:FDA:175.105: Components of adhesives.175.300: Resinous and polymeric components of coatings. (Restricted)175.320: Resinous and polymeric components of coatings for polyolefin films. (Restricted)176.170: Components of paper and paperboard in contact with aqueous and fatty foods. (Restricted)176.180: Components of paper and paperboard in contact with dry foods.Information provided by Michelman®

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Michelman-Michem-Emulsion-61335-Anionic-polyethylene-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.990 - 1.01 g/cc	0.990 - 1.01 g/cc	
Volatiles	64.5 - 65.5 %	64.5 - 65.5 %	
рН	>= 7.0	>= 7.0	Recommended pH of system
	9.7 - 10.7	9.7 - 10.7	
Brookfield Viscosity	<= 50 cP	<= 50 cP	Spindle # 1, rpm 60

Descriptive Properties	Value	Comments	
Appearance	Tan liquid		
Emulsifier Charge	Anionic		
Solids Type	High Density Polyethylene	High Density Polyethylene	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China