

Michelman® Michem® Emulsion 65140 Nonionic polypropylene emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

Description: Nonionic polypropylene emulsion Usage: Michem® Emulsion 65140 is best used as an additive in floor polish and overprint varnish formulations when a high degree of slip resistance is needed. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foam Food Contact Information when manufactured in the USA:

FDA:175.105: Components of adhesives. Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Emulsion-65140-Nonionic-polypropylene-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.980 - 1.00 g/cc	0.980 - 1.00 g/cc	
Volatiles	59.5 - 60.5 %	59.5 - 60.5 %	
pH	>= 7.0	>= 7.0	Recommended pH of system
	7.7 - 9.0	7.7 - 9.0	
Brookfield Viscosity	<= 500 cP	<= 500 cP	Spindle # 2, rpm 60

Descriptive Properties	Value	Comments
Appearance	Amber, translucent liquid	
Emulsifier Charge	Nonionic	
Solids Type	Meleated Polypropylene	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China