

Michelman® Michem® Emulsion 93335 Nonionic polyethylene emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

Description: Nonionic polyethylene emulsion Usage: Michem® Emulsion 93235 is a phenol free additive best used in water based coatings where improved slip, rub resistance, hardness and/or block resistance is needed. Michem® Emulsion 93235 has proven very effective for mar resistance in floor polish formulations as well as mar resistance and shine in car polish formulations. We serve many markets through Michem® Emulsion, including: paint & coatings; fiberglass; inks and overprint varnishes; floor care; wood finishes; automotive care products; building products; carpets; die lubricants; fruit and vegetable coatings; textiles and urethane foam Food Contact Information when manufactured in USA: FDA:175.105: Components of adhesives. Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Emulsion-93335-Nonionic-polyethylene-emulsion.php

| Physical Properties | Metric | English | Comments |
|----------------------|-------------------|-------------------|--------------------------|
| Specific Gravity | 0.990 - 1.01 g/cc | 0.990 - 1.01 g/cc | |
| Volatiles | 64.5 - 65.5 % | 64.5 - 65.5 % | |
| pH | >= 7.0 | >= 7.0 | Recommended pH of system |
| | 9.0 - 10 | 9.0 - 10 | |
| Brookfield Viscosity | <= 50 cP | <= 50 cP | Spindle # 1, rpm 60 |

| Descriptive Properties | Value | Comments |
|------------------------|---------------------------|----------|
| Appearance | Translucent liquid | |
| Emulsifier Charge | Nonionic | |
| Solids Type | High Density Polyethylene | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China