

Michelman® Michem® Guard 25 Nonionic, polyethylene dispersion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

Description: Nonionic, polyethylene dispersion Usage: Michem® Guard 25 is a water based polyethylene dispersion which promotes mar resistance and flattening properties in paint and coating formulations. Typical uses include: Inks and OPVs; Exterior wood and wood composites and Interior furniture and flooring When manufactured in Belgium product meets food contact regulations for: Europe: Euro. Res. AP(2004)1 Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Guard-25-Nonionic-polyethylene-dispersion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.970 - 0.990 g/cc	0.970 - 0.990 g/cc	
Volatiles	57 - 61 %	57 - 61 %	
pH	>= 7.0	>= 7.0	Recommended pH of system
	7.0 - 8.5	7.0 - 8.5	
Brookfield Viscosity	<= 8500 cP	<= 8500 cP	Spindle # 4, rpm 60

Descriptive Properties	Value	Comments
Appearance	White, viscous liquid	
Emulsifier Charge	Nonionic	
Solids Type	Polyethylene	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China