

## Michelman® Michem® Lube 124 Anionic microcrystalline wax emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer

### Material Notes:

Description: Anionic microcrystalline wax emulsion Usage: Michem® Lube 124 as an additive provides release and acts as a detackifier for synthetic and natural rubber. Michem® Lube 124 is used successfully in latex glove formulations. This product also offers slip resistance for adhesives and sealants. Compatible with ingredients used in many industries, including: Automotive care products; Building materials; Can and coil coatings; Concrete; Cordage and twine; Deck stains and sealants; Die lubricants; Fiber sizings; Floor polishes; Furniture coatings; Glass; Gloves, balloons, footwear and mechanical seals; Inks; Packaging films; Pressure-sensitive adhesives; Textiles; Urethane foam and Varnishes Food Contact Information when manufactured in Belgium: FDA: 175.105: Components of adhesives. 175.300: Resinous and polymeric components of coatings. (Restricted) 175.320: Resinous and polymeric components of coatings for polyolefin films. (Restricted) 176.170: Components of paper and paperboard in contact with aqueous and fatty foods. (Restricted) 176.180: Components of paper and paperboard in contact with dry foods When manufactured in Belgium product meets food contact regulations for: Europe: Euro. Res. AP(2004)1 (Restricted) and Commission Regulation (EU) n° 10/2011 (Restricted) Germany: BfR Recommendation XIV (Restricted) and BfR Recommendation XXXVI (Restricted) Information provided by Michelman®

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Michelman-Michem-Lube-124-Anionic-microcrystalline-wax-emulsion.php](http://www.lookpolymers.com/polymer_Michelman-Michem-Lube-124-Anionic-microcrystalline-wax-emulsion.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.960 - 0.980 g/cc	0.960 - 0.980 g/cc	
Volatiles	57 - 59 %	57 - 59 %	
pH	>= 7.0	>= 7.0	Recommended pH of system
	8.7 - 9.7	8.7 - 9.7	
Brookfield Viscosity	400 - 3200 cP	400 - 3200 cP	Spindle # 4, rpm 60

Descriptive Properties	Value	Comments
Appearance	Milky white, semi-viscous liquid	
Emulsifier Charge	Anionic	
Solids Type	Microcrystalline	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China