

Michelman® Michem® Lube 182 Anionic carnauba/paraffin wax emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Description: Anionic carnauba/paraffin wax emulsion Usage: Michem® Lube 182 can provide slip, release and anti-block properties in a number of applications ranging from wood coatings to being blended with synthetic and natural lattices. Michem® Lube 182 is slightly higher in melt point than Michem® Lube 180. This product is also a mar and scratch resistant and water repellent additive in varnishes and other coatings. Compatible with ingredients used in many industries, including: Automotive care products; Building materials; Can and coil coatings; Concrete; Cordage and twine; Deck stains and sealants; Die lubricants; Fiber sizings; Floor polishes; Furniture coatings; Glass; Gloves, balloons, footwear and mechanical seals; Inks; Packaging films; Pressure-sensitive adhesives; Textiles; Urethane foam and Varnishes

Food Contact Information when manufactured in the USA and Belgium: FDA:175.105: Components of adhesives. 175.320: Resinous and polymeric components of coatings for polyolefin films. (Restricted) 176.170: Components of paper and paperboard in contact with aqueous and fatty foods. 176.180: Components of paper and paperboard in contact with dry foods. When manufactured in Belgium Product meets food contact regulations for: Europe: Euro. Res. AP(2004)1 (Restricted) Germany: BfR Recommendation XIV and BfR Recommendation XXXVI (Restricted) Food Contact Information: FDA:175.105: Components of adhesives. 176.170: Components of paper and paperboard in contact with aqueous and fatty foods. 176.180: Components of paper and paperboard in contact with dry foods. Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Lube-182-Anionic-carnaubaparaaffin-wax-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.980 - 1.00 g/cc	0.980 - 1.00 g/cc	
Volatiles	74.5 - 75.5 %	74.5 - 75.5 %	
pH	4.5 - 7.0	4.5 - 7.0	
	1.0 - 12	1.0 - 12	Recommended pH of system
Brookfield Viscosity	<= 15 cP	<= 15 cP	Spindle # 1, rpm 60

Descriptive Properties	Value	Comments
Appearance	White liquid	
Emulsifier Charge	Anionic	
Solids Type	Carnauba/Paraffin wax blend	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China