

Michelman® Michem® Lube 723 Nonionic paraffin wax emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Description: Nonionic paraffin wax emulsion Usage: Michem® Lube 723 provides excellent water repellancy, lubricity, release and wood end check protection when used in the paint and coatings industry. For fiberglass manufacturers, Michem® Lube 723 protects the glass during fiber forming, processing and during post processing . This product is also used in sizings for Gun Roving. Compatible with ingredients used in many industries, including: Automotive care products; Building materials; Can and coil coatings; Concrete; Cordage and twine; Deck stains and sealants; Die lubricants; Fiber sizings; Floor polishes; Furniture coatings; Glass; Gloves, balloons, footwear and mechanical seals; Inks; Packaging films; Pressure-sensitive adhesives; Textiles; Urethane foam and Varnishes Food Contact Information when manufactured in the USA and Belgium: FDA:175.105: Components of adhesives. 175.320: Resinous and polymeric components of coatings for polyolefin films. (Restricted) 176.170: Components of paper and paperboard in contact with aqueous and fatty foods. 176.180: Components of paper and paperboard in contact with dry foods. When manufactured in Singapore product meets food contact regulations for: Germany: BfR Recommendation XIV (Restricted) and BfR Recommendation XXXVI (Restricted) Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Lube-723-Nonionic-paraffin-wax-emulsion.php

| Physical Properties | Metric | English | Comments |
|----------------------|--------------------|--------------------|---------------------|
| Specific Gravity | 0.970 - 0.990 g/cc | 0.970 - 0.990 g/cc | |
| Volatiles | 67.5 - 68.5 % | 67.5 - 68.5 % | |
| pH | 6.0 - 7.5 | 6.0 - 7.5 | |
| Brookfield Viscosity | 10 - 60 cP | 10 - 60 cP | Spindle # 2, rpm 60 |

| Descriptive Properties | Value | Comments |
|------------------------|-----------------------------|----------|
| Appearance | White, low viscosity liquid | |
| Emulsifier Charge | Nonionic | |
| Solids Type | Paraffin | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China