

Michelman® Michem® Wood Coating 75 Anionic paraffin blend emulsion

Category : Fluid , Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Description: Anionic paraffin blend emulsion Usage: Michem® Wood Coating 75 provides excellent water resistance for topical wood coatings. This product works to prevent the swelling of wood in the presence of water, as well as providing great water bead with lower VOC. Michem® Wood Coating products are typically used for: Deck stains and sealants for water beading, water repellence and swell resistance; Building materials for water beading, water repellence, water resistance and slip resistance; and Interior furniture and flooring for water resistance Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Wood-Coating-75-Anionic-paraffin-blend-emulsion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.930 - 0.950 g/cc	0.930 - 0.950 g/cc	
Volatiles	69 - 71 %	69 - 71 %	
pH	>= 6.0	>= 6.0	Recommended pH of system
	8.3 - 10.3	8.3 - 10.3	
Brookfield Viscosity	<= 100 cP	<= 100 cP	Spindle # 2, rpm 60

Descriptive Properties	Value	Comments
Appearance	White, low viscosity liquid	
Emulsifier Charge	Anionic	
Solids Type	Proprietary	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China