

## Mitsui ADMER® QF500A PP Type Polyolefin

Category : Polymer , Thermoplastic , Polyolefin , Polypropylene (PP)

### Material Notes:

ADMER® Adhesive Resin is a modified polyolefin with functional groups, designed to bond to a variety of polyolefins, ionomers, polyamides, ethylene vinyl alcohol (EVOH), polyesters (PET), polycarbonates, polystyrenes and metals such as steel and aluminum. ADMER serves as a tie-layer in unique multi-layer structures to combine properties of different materials, such as gas barrier resins and moisture barrier resins. Available in pellet form, ADMER can be used in a wide variety of coextrusion processes for bottles, tubes, sheets and films. ADMER, a thermoplastic, can be processed easily by: coextrusion blow molding tube coextrusion sheet coextrusion film coextrusion (cast and blown film) coextrusion coating powder coating (metal coating) co-injection ADMER complies with 21 CFR 175, 105. PP based ADMER complies with 21 CFR section 177, 1390, (C) (2) under certain conditions. Information provided by Mitsui Chemicals America, Inc.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Mitsui-ADMER-QF500A-PP-Type-Polyolefin.php](http://www.lookpolymers.com/polymer_Mitsui-ADMER-QF500A-PP-Type-Polyolefin.php)

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in <sup>3</sup>	ASTM D1505
Melt Index of Compound	3.0 g/10 min	3.0 g/10 min	ASTM D1238
	@Temperature 230 Â°C	@Temperature 446 Â°F	

Thermal Properties	Metric	English	Comments
Vicat Softening Point	143 Â°C	289 Â°F	ASTM D1525

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China