

## Momentive Performance Materials IGS3719-D1 Insulating Glass Sealant, Gray

Category : Polymer , Adhesive , Thermoset , Filled/Reinforced Thermoset , Silicone , Silicone, RTV, Construction Grade

### Material Notes:

One-component silicone which cures to form a high strength, high modulus sealant with excellent adhesion to glass. Cure Method: Alkoxy (Neutral). Tack-free time 0.5 hr. Peel Strength 50 lb/in. Sag/slump 0.1 in. Data provided by the manufacturer, GE Silicones. GE Silicones became a part of Momentive Performance Materials in 2006.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Momentive-Performance-Materials-IGS3719-D1-Insulating-Glass-Sealant-Gray.php](http://www.lookpolymers.com/polymer_Momentive-Performance-Materials-IGS3719-D1-Insulating-Glass-Sealant-Gray.php)

Physical Properties	Metric	English	Comments
Density	1.52 g/cc	0.0549 lb/in <sup>3</sup>	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	37	37	ASTM D2240
Tensile Strength, Ultimate	2.10 MPa	305 psi	ASTM D412
Elongation at Break	400 %	400 %	ASTM D412

Processing Properties	Metric	English	Comments
Processing Temperature	25.0 °C	77.0 °F	Cure time to 0.125 in. is 2 hours

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China