

## Momentive Performance Materials IS808 Translucent Adhesive Sealant, General Purpose Paste

Category : Polymer , Adhesive , Thermoset , Silicone , Silicone, RTV, Adhesive/Sealant Grade

### Material Notes:

One-part acetoxy cure. Acetoxy cure silicones are the most commonly used type of RTV materials and are considered GE Silicones' general purpose product line. Typical uses: Use for general purpose, cost-effective sealing and bonding. Cure-in-place electrical insulation. UL approval. Data provided by the manufacturer, GE Silicones. GE Silicones became a part of Momentive Performance Materials in 2006.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Momentive-Performance-Materials-IS808-Translucent-Adhesive-Sealant-General-Purpose-Paste.php](http://www.lookpolymers.com/polymer_Momentive-Performance-Materials-IS808-Translucent-Adhesive-Sealant-General-Purpose-Paste.php)

Physical Properties	Metric	English	Comments
Density	1.04 g/cc	0.0376 lb/in <sup>3</sup>	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	23	23	
Tensile Strength, Ultimate	2.06 MPa	299 psi	
Elongation at Break	450 %	450 %	
Adhesive Bond Strength	0.970 MPa	141 psi	Typical lap shear

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	205 Â°C	401 Â°F	Continuous useful temperature.
Minimum Service Temperature, Air	-60.0 Â°C	-76.0 Â°F	Continuous useful temperature.

Electrical Properties	Metric	English	Comments
Dielectric Constant	2.9	2.9	
	@Frequency 60 Hz	@Frequency 60 Hz	
Dielectric Strength	20.0 kV/mm	508 kV/in	

Processing Properties	Metric	English	Comments
Processing Temperature	25.0 Â°C	77.0 Â°F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

**Tel : +86 021-51131842**

**Mobile : +86 13061808058**

**Skype : lookpolymers**

**Address : United North Road 215, Fengxian District, Shanghai City, China**