

Momentive Performance Materials RTV6445 White Adhesive Sealant, Non-Corrosive High Strength Paste

Category : Polymer , Adhesive , Thermoset , Silicone , Silicone, RTV, Adhesive/Sealant Grade

Material Notes:

One-part heat cure. Typical uses: Thermal barrier for automotive parts. Fabric seam seal. Data provided by the manufacturer, GE Silicones. GE Silicones became a part of Momentive Performance Materials in 2006.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Momentive-Performance-Materials-RTV6445-White-Adhesive-Sealant-Non-Corrosive-High-Strength-Paste.php

Physical Properties	Metric	English	Comments
Density	1.20 g/cc	0.0434 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	38	38	
Tensile Strength, Ultimate	6.03 MPa	875 psi	
Elongation at Break	625 %	625 %	

Electrical Properties	Metric	English	Comments
Dielectric Constant	2.9	2.9	
Dielectric Strength	19.5 kV/mm	495 kV/in	

Processing Properties	Metric	English	Comments
Processing Temperature	125 °C	257 °F	Cure time 45 min at this temperature.

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China