

Monmouth Rubber & Plastics Durafoam[™] PMR 150 EPDM

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Performance Features: Softness, stiffness & density infinitely variable.High Ozone Resistance. High Ultraviolet Resistance. Non-Staining. Made from Heat Resistant EPDM Non-fogging (plasticizer free).Dimensionally Stable (Very Low Shrinkage). Unique Soft, Supple, Real Rubber Feel. Very Fine Cell Structure. Thermoformable – deep draw potential Can be heat and flame laminated. Butt-weldable – Both heat and/or adhesive Bonds well to most pressure sensitive adhesives including economy rubber based adhesives. Available standard in black. Available on special order in custom bright colors. Information provided by Monmouth Rubber & Plastics Corp.

Order this product through the following link: http://www.lookpolymers.com/polymer_Monmouth-Rubber-Plastics-Durafoam-PMR-150-EPDM.php

| Physical Properties | Metric | English | Comments |
|------------------------|---------------------|-----------------|---------------------------------|
| Density | 0.0641 g/cc | 0.00231 lb/in³ | ASTM D3575 |
| | | | |
| Mechanical Properties | Metric | English | Comments |
| Compressive Strength | 0.0345 - 0.0621 MPa | 5.00 - 9.00 psi | Deflection @ 25%; ASTM D1056-00 |
| | | | |
| Descriptive Properties | | Value | Comments |
| Color | | Black | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China