

Multibase Multi-Flex® A 6502 MR Natural TPE Thermoplastic Elastomer

Category : Polymer , Thermoplastic , Elastomer, TPE

Material Notes:

Forms: Pellets Information provided by Multibase

Order this product through the following link:

http://www.lookpolymers.com/polymer_Multibase-Multi-Flex-A-6502-MR-Natural-TPE-Thermoplastic-Elastomer.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.932 g/cc	0.932 g/cc	ASTM 792
Melt Flow	1.7 g/10 min @Load 2.16 kg, Temperature 230 °C	1.7 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	69	69	10 seconds; ASTM D2240
Tensile Strength at Break	5.10 MPa	740 psi	ASTM D412
Elongation at Break	690 %	690 %	Elastic; ASTM D412
Tear Strength	36.8 kN/m	210 pli	ASTM D624

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China