

Multibase Multi-Flex® TPE RP 6568 CT BLK

Category : Polymer , Thermoplastic , Elastomer, TPE , Thermoplastic Elastomer, Melt-Processible Rubber

Material Notes:

Ash is 1.35%. Multi-Flex TPE contains Kraton™ G.Data provided by Multibase.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Multibase-Multi-Flex-TPE-RP-6568-CT-BLK.php

Physical Properties	Metric	English	Comments
Density	0.9164 g/cc	0.03311 lb/in ³	ASTM D792
Linear Mold Shrinkage	0.016 cm/cm	0.016 in/in	ASTM D955
Melt Flow	13 g/10 min	13 g/10 min	(Condition L) ASTM D-1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	48	48	10 sec; ASTM D-2240
Tensile Strength, Ultimate	4.00 MPa	580 psi	ASTM D412
Elongation at Break	775 %	775 %	ASTM D412
Tear Strength	25.0 kN/m	143 pli	ASTM D624

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China