

Multibase Multi-Flex® TPO D 5302 Q

Category : Polymer , Thermoplastic , Elastomer, TPE , Thermoplastic Olefinic Elastomer (TPO)

Material Notes:

Data provided by Multibase.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Multibase-Multi-Flex-TPO-D-5302-Q.php

Physical Properties	Metric	English	Comments
Density	0.8995 g/cc	0.03250 lb/in ³	ASTM D792-91
Linear Mold Shrinkage	0.011 cm/cm	0.011 in/in	ASTM D955-89
Melt Flow	0.95 g/10 min	0.95 g/10 min	(Condition L) ASTM D-1238-94a

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	58	58	10 sec; ASTM D-2240-95
Tensile Strength, Ultimate	26.3 MPa	3810 psi	ASTM D638-95
Elongation at Break	593 %	593 %	ASTM D638-95
Flexural Modulus	0.616 GPa	89.3 ksi	Secant 1%; ASTM D-790-95
Tear Strength	159 kN/m	907 pli	ASTM D624-95

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China