

## Mytex Polymers AS65KWLGUS Polypropylene, Talc filled, Compounded

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene with 10% Talc Filler

### Material Notes:

Description: Talc filled compounded polypropylene with high stiffness, superior impact balance, surface hardness and extremely low gloss. Key Applications: Non-painted instrument panel. Information provided by Mytex Polymers

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Mytex-Polymers-AS65KWLGUS-Polypropylene-Talc-filled-Compounded.php](http://www.lookpolymers.com/polymer_Mytex-Polymers-AS65KWLGUS-Polypropylene-Talc-filled-Compounded.php)

Physical Properties	Metric	English	Comments
Density	1.08 g/cc	0.0390 lb/in <sup>3</sup>	ASTM D792
Melt Flow	15 g/10 min	15 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	75	75	ASTM D785
Tensile Strength, Yield	23.0 MPa	3340 psi	50 mm/min; ASTM D638
Flexural Modulus	2.50 GPa	363 ksi	Tangent; 1.3 mm/min; ASTM D790
Izod Impact, Notched	5.50 J/cm @Temperature 23.0 °C	10.3 ft-lb/in @Temperature 73.4 °F	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	120 °C	248 °F	ASTM D648

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China