

Mytex Polymers AS88L-01 Polypropylene, Compounded, Elastomer

Category : Polymer , Thermoplastic , Elastomer, TPE , Polypropylene (PP)

Material Notes:

Description: AS88L-01 is a compounded, elastomer modified polypropylene with good impact and excellent material flow properties. This product is designed for painted and mold-in-color applications and is particularly well suited for thin wall bumper fascias applications. Key

Applications: Bumper fascias, cladding and bodyside molding Information provided by Mytex Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_Mytex-Polymers-AS88L-01-Polypropylene-Compounded-Elastomer.php

Physical Properties	Metric	English	Comments
Density	1.04 g/cc	0.0376 lb/in ³	ASTM D792
Melt Flow	26 g/10 min	26 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	55	55	15 sec; ISO 868
Tensile Strength, Yield	17.0 MPa	2470 psi	50 mm/min; ISO 527
Flexural Modulus	1.73 GPa	251 ksi	Chord; 2 mm/min; ISO 178
Izod Impact, Notched (ISO)	45.0 kJ/m ² @Temperature 23.0 °C	21.4 ft-lb/in ² @Temperature 73.4 °F	ISO 180

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	98.0 °C	208 °F	ISO 75-1

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China