

NCMT NanoPAC™ HS402 High Performance Polypropylene Nanocomposite

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

Applications: Electrical Appliances Information provided by Nano Composite Materials Technology Limited

Order this product through the following link:

http://www.lookpolymers.com/polymer_NCMT-NanoPAC-HS402-High-Performance-Polypropylene-Nanocomposite.php

Physical Properties	Metric	English	Comments
Density	1.03 g/cc	0.0372 lb/in ³	NCMT Method
Melt Flow	55 g/10 min @Load 2.16 kg, Temperature 230 °C	55 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	23.0 MPa	3340 psi	ASTM D638
Elongation at Break	<= 60 %	<= 60 %	ASTM D638
Tensile Modulus	1.70 GPa	247 ksi	ASTM D638
Izod Impact, Notched	0.500 J/cm	0.937 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	100 °C	212 °F	Deflection Temp.; ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China