

ND Industries 440 High pressure Sealant

Category : Polymer , Adhesive , Thermoset

Material Notes:

Pneumatic and hydraulic sealant fluid, for power and gas system connections

Order this product through the following link:

http://www.lookpolymers.com/polymer_ND-Industries-440-High-pressure-Sealant.php

Physical Properties	Metric	English	Comments
Viscosity	12000 - 16000 cP	12000 - 16000 cP	

Mechanical Properties	Metric	English	Comments
Shear Strength	>= 68.9 MPa	>= 10000 psi	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	30.0 min	0.500 hour	With Primer (Fixture)
	240 min	4.00 hour	On steel (fixture)
	1440 min	24.0 hour	On Steel (Full)
	1440 min	24.0 hour	With Primer (Full)

Descriptive Properties	Value	Comments
Color	Purple	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China