

ND Industries 444 High pressure Sealant

Category : Polymer , Adhesive , Thermoset

Material Notes:

Very high strength hydraulic sealant. Non-shrink, high vibration and shock resistance

Order this product through the following link:

http://www.lookpolymers.com/polymer_ND-Industries-444-High-pressure-Sealant.php

Physical Properties	Metric	English	Comments
Viscosity	300 - 500 cP	300 - 500 cP	

Mechanical Properties	Metric	English	Comments
Shear Strength	>= 68.9 MPa	>= 10000 psi	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	10.0 min	0.167 hour	With Primer (Fixture)
	60.0 min	1.00 hour	On steel (fixture)
	1440 min	24.0 hour	On Steel (Full)
	1440 min	24.0 hour	With Primer (Full)

Descriptive Properties	Value	Comments
Color	Brown	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China