

NIZHNEKAMSKNEFTEKHIM PP 1500P (V30G) Propylene Homopolymer

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

Product obtained by polymerization of propylene in presence of complex metalorganic catalysts. It incorporates increased long-term thermal stability, thermal-oxidative degradation resistance when PP is produced, processed and PP-made articles are exploited. Information provided by manufacturer

Order this product through the following link:

http://www.lookpolymers.com/polymer_NIZHNEKAMSKNEFTEKHIM-PP-1500P-V30G-Propylene-Homopolymer.php

Physical Properties	Metric	English	Comments
Melt Flow	15 - 20 g/10 min	15 - 20 g/10 min	ASTM D1238/L
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Flexural Modulus	>= 1.40 GPa	>= 203 ksi	ASTM D790
Izod Impact, Notched	>= 0.250 J/cm	>= 0.468 ft-lb/in	ASTM D256
	@Temperature 23.0 °C	@Temperature 73.4 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China