

NOVA Chemicals Dytherm® 370R Expandable Polystyrene

Category: Polymer, Thermoplastic, Polystyrene (PS), Expanded Polystyrene (EPS)

Material Notes:

This is a special grade consisting of spherical beads of a blend of polystyrene-polyphenylene ether containing pentane as expansion agent, typically used for medium density foam with improved thermal resistance. Applications: This grade is used for medium density foam with wall-thickness generally greater than or equal to 10 mm and with improved thermal resistance. Typical applications include hot-water insulation and automotive parts (interior and exterior). Processing of DYTHERM beads on pressurized batch pre-expander is recommended. It can be process on a continuous pre-expander when higher densities are acceptable. This grade should not be used for food contact applications. Information provided by NOVA Chemicals.

Order this product through the following link:

http://www.lookpolymers.com/polymer_NOVA-Chemicals-Dytherm-370R-Expandable-Polystyrene.php

Physical Properties	Metric	English	Comments
Bulk Density	0.620 g/cc	0.0224 lb/in³	
Density	>= 0.0350 g/cc	>= 0.00126 lb/in³	Minimum achievable; Single stage pre-expansion in continuous expander at atmospheric pressure
	0.0350 - 0.100 g/cc	0.00126 - 0.00361 lb/in³	Normal molded density assuming cost optimized selection of processing conditions.
Bead Size	0.300 - 0.700 mm	0.0118 - 0.0276 in	Breda Laboratory Analytical Methods 90.30
	0.400 - 0.700 mm	0.0157 - 0.0276 in	

Chemical Properties	Metric	English	Comments
Styrene Content	<= 0.10 %	<= 0.10 %	Residual Styrene Monomer Content per Breda Laboratory Analytical Methods 90.16
Blowing Agent Content	>= 5.8 %	>= 5.8 %	Breda Laboratory Analytical Methods 90.18

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China