

NOVA Chemicals Novapol® HE-Y449-A HDPE Extrusion Resin

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Extruded

Material Notes:

Features: High ESCR, good toughness, good chemical resistance, good processability. Applications: Pipe coatings, profile extrusions, sheet extrusion for thermoforming, corrugated tubing, conduit. Data provided by the manufacturer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_NOVA-Chemicals-Novapol-HE-Y449-A-HDPE-Extrusion-Resin.php

Physical Properties	Metric	English	Comments
Density	0.949 g/cc	0.0343 lb/in ³	ASTM D792
Water Absorption	0.010 %	0.010 %	ASTM D570
Environmental Stress Crack Resistance	>= 1000 hour	>= 1000 hour	F50; ASTM D1693
Oxidative Induction Time (OIT)	10 min	10 min	ASTM D3895
Melt Flow	0.40 g/10 min @Load 2.16 kg, Temperature 190 °C	0.40 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	61	61	ASTM D2240
Tensile Strength, Yield	24.0 MPa	3480 psi	ASTM D638
Elongation at Break	650 %	650 %	ASTM D638
Flexural Modulus	1.14 GPa	165 ksi	Tangent; ASTM D790
Izod Impact, Notched	0.800 J/cm	1.50 ft-lb/in	Notched/Unnotched not specified; ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	130 °C	266 °F	ASTM D3417
Vicat Softening Point	124 °C	255 °F	ASTM D1525
Brittleness Temperature	<= -100 °C	<= -148 °F	ASTM D696

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China