

NOVA Chemicals Novapol® LE-0520-A LDPE Extrusion Resin (discontinued **)

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE , Low Density Polyethylene (LDPE), Extrusion Grade

Material Notes:

Features: easy processing, good dispersion. Applications: Additive and color concentrates for film and molding. Data provided by the manufacturer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_NOVA-Chemicals-Novapol-LE-0520-A-LDPE-Extrusion-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.920 g/cc	0.0332 lb/in ³	ASTM D792
Melt Flow	4.5 g/10 min @Load 2.16 kg, Temperature 190 °C	4.5 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Processing Properties	Metric	English	Comments
Melt Temperature	180 - 225 °C	356 - 437 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China