

NOVA Chemicals Novapol® TI-0338-A MDPE Masterbatch Resin

Category : Polymer , Thermoplastic , Polyethylene (PE) , MDPE

Material Notes:

Molded Plaque Properties. Features: Hexene Copolymer, excellent impact strength, excellent ESCR.Applications: large parts, agricultural storage tanks.Data provided by the manufacturer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_NOVA-Chemicals-Novapol-TI-0338-A-MDPE-Masterbatch-Resin.php

Physical Properties	Metric	English	Comments
Density	0.938 g/cc	0.0339 lb/in ³	ASTM D792
Melt Flow	3.5 g/10 min @Load 2.16 kg, Temperature 190 °C	3.5 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238
Crystallinity	56 %	56 %	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	29.1 MPa	4220 psi	ASTM D638
Tensile Strength, Yield	20.6 MPa	2990 psi	ASTM D638
Elongation at Break	1000 %	1000 %	ASTM D638
Elongation at Yield	12 %	12 %	ASTM D638
Flexural Modulus	0.702 GPa	102 ksi	ASTM D790
Izod Impact, Notched	1.82 J/cm @Thickness 3.20 mm	3.41 ft-lb/in @Thickness 0.126 in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	129 °C	264 °F	ASTM D3417
Crystallization Temperature	114 °C	237 °F	ASTM D3417
Deflection Temperature at 0.46 MPa (66 psi)	58.0 °C	136 °F	ASTM D1525
Vicat Softening Point	122 °C	252 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China