

NOVA Chemicals Sclair® 2607-UV9 HDPE Injection Molding Resin (discontinued **)

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Injection Molded

Material Notes:

Features: Excellent stiffness, good impact resistance, low warpage. Applications: Roll-out carts. Data provided by the manufacturer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_NOVA-Chemicals-Sclair-2607-UV9-HDPE-Injection-Molding-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.947 g/cc	0.0342 lb/in ³	ASTM D792
Melt Flow	4.8 g/10 min @Load 2.16 kg, Temperature 190 °C	4.8 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	65	65	ASTM D2240
Tensile Strength, Yield	22.0 MPa	3190 psi	ASTM D638
Elongation at Break	1000 %	1000 %	ASTM D638
Flexural Modulus	0.850 GPa	123 ksi	ASTM D790

Thermal Properties	Metric	English	Comments
Vicat Softening Point	122 °C	252 °F	ASTM D1525

Processing Properties	Metric	English	Comments
Melt Temperature	170 - 215 °C	338 - 419 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China