

Nabaltec GRANALOX® NM 9916 F Ceramic Body

Category : Ceramic , Oxide , Aluminum Oxide

Material Notes:

Nabaltec's GRANALOX® Ceramic bodies are produced under rigid quality control of green and sintered density, shrinkage, porosity, loss on ignition and granulate size. The properties of the corundum are tailored to the application areas in which the material is used such as wear resistance, high temperature stability, good electrical insulation, thermal conductivity and corrosion resistance. Used in engineering ceramics. Information provided by Nabaltec.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nabaltec-GRANALOX-NM-9916-F-Ceramic-Body.php

Physical Properties	Metric	English	Comments
Bulk Density	1.10 - 1.20 g/cc	0.0397 - 0.0434 lb/in ³	
Density	3.88 - 3.92 g/cc	0.140 - 0.142 lb/in ³	Sintered
Moisture Absorption at Equilibrium	0.30 - 0.50 %	0.30 - 0.50 %	
Loss On Ignition	5.0 %	5.0 %	
Particle Size	80 - 120 µm	80 - 120 µm	Mean Granulate Size

Thermal Properties	Metric	English	Comments
Shrinkage	17 - 18 %	17 - 18 %	linear

Component Elements Properties	Metric	English	Comments
Al ₂ O ₃	99.6 %	99.6 %	
Na ₂ O	0.10 %	0.10 %	

Processing Properties	Metric	English	Comments
Sintering Temperature	1600 - 1700 °C	2910 - 3090 °F	Interval (dense ceramic parts)
	1620 °C	2950 °F	
	@Time 7200 sec	@Time 2.00 hour	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China