

NanoAmor 95%, OD/WT/L: 40-70/5-30 nm/0.5-5 um Multi-Walled Carbon Nanotubes

Category : Carbon

Material Notes:

Applications Additives in polymers Catalysts Electron field emitters for cathode ray lighting elements, flat panel display, gas-discharge tubes in telecom networks Electromagnetic-wave absorption and shielding Energy conversion Lithium-battery anodes Hydrogen storage Nanotube composites (by filling or coating); Nanoprobes for STM, AFM, and EFM tips, nanolithography, nanoelectrodes, drug delivery, sensors Reinforcements in composites Supercapacitor Information provided by NanoAmor Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_NanoAmor-95-ODWTL-40-705-30-nm05-5-um-Multi-Walled-Carbon-Nanotubes.php

Physical Properties	Metric	English	Comments
Apparent Bulk Density	0.340 g/cc	0.0123 lb/in ³	
Particle Size	0.0050 - 0.030 μm	0.0050 - 0.030 μm	wall thickness
	0.040 - 0.070 μm	0.040 - 0.070 μm	outside diameter
Specific Surface Area	150 - 400 m ² /g	150 - 400 m ² /g	

Descriptive Properties	Value	Comments
Color	black	
Length (um)	0.5-5	
Purity (vol% carbon nanotubes), min	95	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China