

NanoAmor 99%, OD/L: 40-60 nm/1-2 um Multi-Walled Carbon Nanotubes

Category : Carbon

Material Notes:

Applications Additives in polymers Catalysts Electron field emitters for cathode ray lighting elements, flat panel display, gas-discharge tubes in telecom networks Electromagnetic-wave absorption and shielding Energy conversion Lithium-battery anodes Hydrogen storage Nanotube composites (by filling or coating); Nanoprobes for STM, AFM, and EFM tips, nanolithography, nanoelectrodes, drug delivery, sensors Reinforcements in composites Supercapacitor Information provided by NanoAmor Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_NanoAmor-99-ODL-40-60-nm1-2-um-Multi-Walled-Carbon-Nanotubes.php

Physical Properties	Metric	English	Comments
Particle Size	0.040 - 0.060 μm	0.040 - 0.060 μm	outside diameter
Specific Surface Area	60 - 70 m^2/g	60 - 70 m^2/g	

Descriptive Properties	Value	Comments
Color	black	
Length (um)	1-2	
Purity (vol% carbon nanotubes), min	99	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China