

## Nanocyl PLASTICYL™ PBT1501 Polybutylene Terephthalate - Carbon Nanotube Masterbatch

Category : Polymer , Thermoplastic , Polyester, TP , Polybutylene Terephthalate (PBT) , Polybutylene Terephthalate (PBT), Carbon Fiber Filled

### Material Notes:

PLASTICYL™ is a family of Multi-Wall Carbon Nanotube (MWNT) thermoplastic concentrates for applications requiring superior electrical conductivity and electrostatic discharge (ESD) properties. PLASTICYL™ PBT1501 is a conductive masterbatch based on polybutylene terephthalate. Because of its high flow formulation, PLASTICYL™ PBT1501 is ideal for standard injection molding and extrusion processes. Applications: ESD (Electrostatic Discharge) and electrically conductive parts E&E, automotive, industrial injection molding, extrusion. Benefits: Electrical conductivity at low loading, Retention of key mechanical properties, Easier processing.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Nanocyl-PLASTICYL-PBT1501-Polybutylene-Terephthalate-Carbon-Nanotube-Masterbatch.php](http://www.lookpolymers.com/polymer_Nanocyl-PLASTICYL-PBT1501-Polybutylene-Terephthalate-Carbon-Nanotube-Masterbatch.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.30 g/cc	1.30 g/cc	ISO 1183
Filler Content	14 - 16 %	14 - 16 %	Carbon Nanotube Loading
High Load Melt Index	<= 0.88 g/10 min @Load 20.0 kg, Temperature 250 °C	<= 0.88 g/10 min @Load 44.1 lb, Temperature 482 °F	4 mm; Non-standard Test

Thermal Properties	Metric	English	Comments
Melting Point	227 °C	441 °F	ISO 11357-1,-3

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China